

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.10.2016

Version number 11

Revision: 31.10.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** TYTAN PROFESSIONAL PU FOAM CLEANER 500 ml
- **Article number:** F-007/4
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
Construction chemicals
- **Application of the substance / the mixture** Remover
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Selena Yapı Malzemeleri Sanayi ve Ticaret Ltd. Şti.
Şerifali Mah.Kız Kalesi sok.ECT Plaza No:15/1 Ümraniye-İstanbul Turkey
tel: + 90 216 466 26 26, fax: +90 216 540 89 00
e-mail: info@selenaturk.com.tr, www.selenaturk.com.tr
- **Further information obtainable from:** info@selenaturk.com.tr
- **1.4 Emergency telephone number:** European emergency number: 112 (24h)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Eye Irrit. 2 H319	Causes serious eye irritation.
STOT SE 3 H336	May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02



GHS07

- **Signal word** Danger
- **Hazard-determining components of labelling:**
acetone
- **Hazard statements**
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
- **Precautionary statements**
P102 Keep out of reach of children.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.10.2016

Version number 11

Revision: 31.10.2016

Trade name: TYTAN PROFESSIONAL PU FOAM CLEANER 500 ml

(Contd. of page 1)

- P271 Use only outdoors or in a well-ventilated area.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

• **Additional information:**

- Do not pierce or burn, even after use.
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 Do not spray on an open flame or other ignition source.
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 EUH66 Repeated exposure may cause skin dryness or cracking.

• **2.3 Other hazards**

• **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
 • **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

• **3.2 Chemical characterisation: Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

• **Dangerous components:**

CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx	acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	60.0 - 80.0%
CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37-0001	dimethyl ether ⚠ Flam. Gas 1, H220; Press. Gas C, H280	< 12.0%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-31-xxxx	butane ⚠ Flam. Gas 1, H220; Press. Gas C, H280	< 12.0%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-21194869440-21-xxxx	propane ⚠ Flam. Gas 1, H220; Press. Gas C, H280	< 12.0%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane ⚠ Flam. Gas 1, H220; Press. Gas C, H280	< 12.0%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• **4.1 Description of first aid measures**

- **General information:** Immediately remove any clothing soiled by the product.

• **After inhalation:**

- Supply fresh air and to be sure call for a doctor.
 Use a respiratory bag or breathing device.
 In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

• **After eye contact:**

- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• **After swallowing:**

- Rinse out mouth and then drink plenty of water.
 Do not induce vomiting; call for medical help immediately.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.10.2016

Version number 11

Revision: 31.10.2016

Trade name: TYTAN PROFESSIONAL PU FOAM CLEANER 500 ml

(Contd. of page 2)

· 4.2 Most important symptoms and effects, both acute and delayed

Stupor.
Headache.
Unconsciousness.
Coughing.
Nausea.
Dizziness.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media**· Suitable extinguishing agents:**

Carbon dioxide.
Water spray.
Fire-extinguishing powder.
Alcohol resistant foam.

· 5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.
Formation of toxic gases is possible during heating or in case of fire.

· 5.3 Advice for firefighters**· Protective equipment:**

Do not inhale explosion gases or combustion gases.
Wear self-contained respiratory protective device.

· Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.
Do not breathe gas / fumes / vapour / spray.
Use respiratory protective device against the effects of fumes / dust / aerosol.
Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions: Do not allow to enter sewers / surface or ground water.**· 6.3 Methods and material for containment and cleaning up:**

Allow to evaporate.
Ensure adequate ventilation.

· 6.4 Reference to other sections See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
Ensure good ventilation / exhaustion at the workplace.
Open and handle receptacle with care.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
Do not spray onto a naked flame or any incandescent material.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.10.2016

Version number 11

Revision: 31.10.2016

Trade name: TYTAN PROFESSIONAL PU FOAM CLEANER 500 ml

(Contd. of page 3)

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:**
Store away from oxidising agents.
Do not store together with reducing agents, heavy-metal compounds, acids and alkalis.
- **Further information about storage conditions:**
Store in vertical position in closed original containers.
Store at temperature from +5 °C to +30 °C.
Protect from heat and direct sunlight.
Store under lock and key and out of the reach of children.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

CAS: 67-64-1 acetone

WEL	Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm
-----	--

CAS: 115-10-6 dimethyl ether

WEL	Short-term value: 958 mg/m ³ , 500 ppm Long-term value: 766 mg/m ³ , 400 ppm
-----	---

CAS: 106-97-8 butane

WEL	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
-----	---

- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Do not eat, drink, smoke or sniff while working.
Avoid contact with the eyes and skin.
- **Respiratory protection:** Use suitable respiratory protective device in case of insufficient ventilation.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product / the substance / the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

- **Material of gloves**

Rubber gloves
Plastic gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 31.10.2016

Version number 11

Revision: 31.10.2016

Trade name: TYTAN PROFESSIONAL PU FOAM CLEANER 500 ml

(Contd. of page 4)

application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Safety glasses

· **Body protection:** Protective work clothing.

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Aerosol
Colour:	Colorless
Odour:	Characteristic

· **Change in condition**

Melting point/Melting range:	-65.4 °C (acetone)
Boiling point/Boiling range:	56.2 °C (acetone, 1,013 hPa)

· Flash point:	< -20 °C (acetone)
· Self-igniting:	> +365 °C (butane)
· Danger of explosion:	Heating may cause an explosion.
· Explosion limits:	
Oxidising properties	Extremely flammable.
· Vapour pressure at 20 °C:	> 500 kPa
· Density:	Not determined
· Solubility in / Miscibility with water:	Soluble
· 9.2 Other information	No further relevant information available

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
To avoid thermal decomposition do not overheat.
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Reacts with oxidising agents.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** Avoid contact with other chemicals.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

GB

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.10.2016

Version number 11

Revision: 31.10.2016

Trade name: TYTAN PROFESSIONAL PU FOAM CLEANER 500 ml

(Contd. of page 5)

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

CAS: 67-64-1 acetone

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)
Inhalative	LC50/4h	7.5 mg/l (fish)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

CAS: 67-64-1 acetone

EC50 | 10 mg/kg (daphnia)

- **12.2 Persistence and degradability** Easily biodegradable
- **12.3 Bioaccumulative potential** Non significant accumulation in organisms
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Due to available data on eliminability/decomposition and bioaccumulation potential a prolonged damage of the environment is unlikely.
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **European waste catalogue**

14 00 00	WASTE ORGANIC SOLVENTS, REFRIGERANTS AND PROPELLANTS (EXCEPT 07 AND 08)
14 06 00	waste organic solvents, refrigerants and foam/aerosol propellants

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 31.10.2016

Version number 11

Revision: 31.10.2016



Trade name: TYTAN PROFESSIONAL PU FOAM CLEANER 500 ml

(Contd. of page 6)

14 06 03*	other solvents and solvent mixtures
15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED
15 01 00	packaging (including separately collected municipal packaging waste)
15 01 05	composite packaging

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number · ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name · ADR · IMDG · IATA	1950 AEROSOLS AEROSOLS AEROSOLS, flammable
· 14.3 Transport hazard class(es) · ADR	
	
· Class · Label	2 5F Gases. 2.1
· IMDG, IATA	
	
· Class · Label	2.1 2.1
· 14.4 Packing group · ADR, IMDG, IATA	Not applicable
· 14.5 Environmental hazards: · Marine pollutant:	No.
· 14.6 Special precautions for user · Danger code (Kemler): · EMS Number:	Warning: Gases. - F-D,S-U
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Transport category	1L 2

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.10.2016

Version number 11

Revision: 31.10.2016

Trade name: TYTAN PROFESSIONAL PU FOAM CLEANER 500 ml

(Contd. of page 7)

· Tunnel restriction code	D
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P3a FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 28, 29
- **Other regulations, limitations and prohibitive regulations**
- **Substances of very high concern (SVHC) according to REACH, Article 57**
None of the ingredients is listed.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
- **Department issuing SDS:** Product safety department.
- **Abbreviations and acronyms:**
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern
vPvB: very Persistent and very Bioaccumulative
Flam. Gas 1: Flammable gases – Category 1
Aerosol 1: Aerosols – Category 1
Press. Gas C: Gases under pressure – Compressed gas
Flam. Liq. 2: Flammable liquids – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3